



▶ 1" STRUCTURAL ▶ 3/4" NONSTRUCTURAL ▶ STOCKING 14', 16', 18' AND 20' LENGTHS

Ply-Trim® Stair Stringer Components

- ▶ 100% USABLE MATERIAL
- ▶ COST EFFECTIVE SOLUTIONS – STRAIGHT TRUCKS OF 16' LENGTHS, NO RANDOM TALLIES (BETTER INVENTORY CONTROL)
- ▶ CNC MACHINE READY
- ▶ UNIFORM THICKNESS



Technical Specifications

THICKNESS:	3/4" NONSTRUCTURAL AND 1" STRUCTURAL
STANDARD FINISH:	PRIME COATED – 4 SIDES
STANDARD DEPTHS:	9-1/4" AND 11-1/4"
STANDARD LENGTHS:	14', 16', 18' AND 20'
SPECIAL ORDERS:	UPON REQUEST – CALL FOR QUOTE

Engineering Specifications – ASTM – D198

STATIC BENDING – EDGE (BEAM) – F_b	= 4,100 PSI
COMPRESSION SHORT MEMBER	= 2,500 PSI
COMPRESSION LONG MEMBER	= 3,000 PSI

Structural Stair Stringer Physical & Packaging Specifications

SIZE	WEIGHT/ LIN. FT.	APPROX. WEIGHT PER UNIT/16' LENGTH	PIECES PER UNIT	APPROX. LIN. FT. PER TRUCK LOAD
3/4" x 9-1/4" (7 PLY)	1.45 lbs.	2320 lbs.	105	26,880
3/4" x 11-1/4" (7 PLY)	1.97 lbs.	2648 lbs.	84	21,504
1" x 9-1/4" (10 PLY)	2.28 lbs.	2736 lbs.	75	19,200
1" x 11-1/4" (10 PLY)	2.78 lbs.	2669 lbs.	60	15,360



PLY-TRIM, INC.
 550 N. Meridian Road
 Youngstown, OH 44509
 1-800-PLY-TRIM
 330-799-7876
 Fax: 330-799-2908
 www.plytrim.com

PLY-TRIM WEST, INC.
 2920 S. Cushman Drive
 Tacoma, WA 98409
 1-800-545-4454
 253-572-7300
 Fax 253-272-5270
 www.ply-trimwest.com



PLY-TRIM
550 North Meridian Road
Youngstown, OH 44509

1-800-PLY-TRIM
Ph : 1-330-799-7876
Fax: 1-330-799-2908

PLY-TRIM STAIR STRINGERS & COMPONENTS ADVANTAGES, FEATURES & BENEFITS

- 1. One Stop Shopping at the Ply-Trim Companies.**
Our Program is designed to provide Stair Stringers and OSB Treads, on the same truck! With skyrocketing Freight and Inventory Costs, Stock Turns are more and more valuable. Our timely shipments and ability to ship a combination of Stringers and Treads allow you to control your Inventory Costs.
- 2. Ply-Trim Stringers and Stair Treads are Structurally Rated.**
We have Engineering Specifications to back our Products. You know exactly what you are getting with the Ply-Trim Stair Components. Stringers are Tested per ASTM D198-05 Specification; OSB Treads per APA Guidelines and PS 2-92 & PS 2-04.
- 3. Consistent Supply**
Ply-Trim Companies has two (2) Manufacturing facility locations – Tacoma, Washington and Youngstown, Ohio. We have been in business for over twenty-eight (28) years. Our reputation speaks for itself!
- 4. Competitive Pricing**
With two locations to serve you, we can lower delivered costs.
- 5. 100% Usable Material**
Both the PT Stringer product and the APA OSB Tread products are engineered to precise specifications, virtually eliminating the typical problems that arise with solid sawn materials.
- 6. Lengths and Widths that Work for You**
Stringers are manufactured in 14', 16', 18', and 20' lengths in both 9 1/4" and 11 1/4" widths. OSB Treads are available in 4', 8', 12', 16' lengths; Standard Stair Tread Widths are available in widths of 10 1/8" up to 12 1/4". CUSTOM WIDTHS ALSO AVAILABLE. Please call with your request.
- 7. CNC Machine Ready**
- 8. PT Engineered Stair Stringers & OSB Treads Eliminate Waste**
Uniform thickness, no Cupping, Warping, Twisting or Moisture Issues like Standard Lumber. Straight and Consistent – Ply-Trim Stair Stringers provide a much more consistent substrate for Routing Machines by eliminating shrinkage and costly, time consuming machine adjustments.